

## **JP2002096105**

Publication Title:

**METHOD FOR MANUFACTURING HIGH-STRENGTH STEEL PIPE**

Abstract:

Abstract of JP 2002096105

(A) PROBLEM TO BE SOLVED: To manufacture a high-strength steel pipe which restrains inner flaws from being caused and which is excellent in resistance to sulfide, stress and corrosion cracking. SOLUTION: Seamless pipes are manufactured by the direct hot rolling of billets made by continuously casting low-alloy steel containing C of 0.2-0.3 wt.%, Si of 0.1-0.3 wt.%, Mn of 0.1-0.3 wt.%, P of 0.15 wt.% or less, S of 0.002 wt.% or less, Cr of 0.5-1.5 wt.%, Mo of 0.2-1.0 wt.%, Nb of 0.01-0.05 wt.%, B of 0.0005-0.005 wt.%, O of 0.005 wt.% or less and H of 0.0005 wt.%, and the seamless pipes are then subjected to heat treatment such as quenching and tempering.

-----  
Courtesy of <http://v3.espacenet.com>











【図1】



【図2】



フロントページの続き

(51)Int.Cl. <sup>7</sup>		識別記号	F I	ターム(参考)
B 2 2 D	11/12		B 2 2 D 11/12	A
C 2 1 D	9/08		C 2 1 D 9/08	E
// C 2 2 C	38/00	3 0 1	C 2 2 C 38/00	3 0 1 Z
	38/32		38/32	

(72)発明者 橋爪 修司  
東京都千代田区丸の内一丁目1番2号 日  
本鋼管株式会社内

Fターム(参考) 4E002 AA04 AB06 BB08 BD02 CB03  
CB10  
4K042 AA06 BA01 BA07 CA02 CA03  
CA06 CA08 CA09 CA12 CA13  
CA14 DA01 DA02 DC02 DD02  
DE02